

TODA Benzine N 15W-40

Product Descriptions

TODA Benzine N 15W-40 is a range of quality premium mineral motor oils designed to provide a high level of performance and protection under most operating conditions.

Quality Attributes

- Good wear protection
- Good oxidation stability
- Good engine cleanliness
- High quality base oils
- Excellent protection against sludge build up
- Good high temperature protection

Applications

TODA Benzine N is suitable for use in automotive gasoline and diesel engines where the manufacturer recommends an API SN/CF or earlier specification

Specifications

API SN/CF

Typicals

Density @15 °C, kg/l	0.87
Viscosity @40 °C mm ² /s	105
Viscosity @100 °C mm ² /s	14.5
Viscosity Index	142
Pour Point, °C	-33
Flash Point COC, °C	220
Total Base Number, mgKOH/g	5.8

Packing Size 1 liter, 4 liters, 18 liters, 200 liters

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

Toda Oil Japan 15/9 Buddhamonthon Sai 2 Rd., Taweewattana Bangkok 10170, Phone: Sales +66 (80)515-2424

Website: www.todaoiljapan.com E-mail: sales@todaoiljapan.com