

TODA CVT

Product Descriptions

TODA CVT is a 100% synthetic gear oil for CVT. It comes with HTC technology (High Torque Capacity), with maximum torque. To meet the accelerated speed in all driving conditions. At the same time, it also serves to protect and reduce vibration in the CVT transmission.

Quality Attributes

- Provides consistent shift performance
- Excellent oxidation stability
- Protects against rust and corrosion
- Excellent EP and anti-wear performance
- Excellent anti-shudder durability performance
- Specific friction properties for CVTs

Applications

- Suitable for use in various CVTs (both pushbelt systems and chain systems) by Japanese and European car manufacturers

Specifications

BMW/Mini Cooper EZL799/799A

Chrysler/Dodge/Jeep NS-2/Mopar CVTF+4

BMW ATF 6 (83 22 2 355 599)

Daihatsu Ammix CVTF DC/DFC/DFE

GM/Saturn DEX-CVT

Honda HMMF(without starting clutch)/HCF2

Hyundai/Kia CVT-J1/SP III (CVT model)

Mazda JWS 3320

MB 236.20

Mitsubishi SP-III (only in CVT)/CVTF-J1/J4/J4+

Nissan NS-1/NS-2/NS-3

Punch CVT

Subaru ECVT/ICVT/ICVT FG/NS-2

Subaru Lineartronic High Torque (HT) CVTF

Subaru Lineartronic chain CVTF/CVTF II

Suzuki CVTF TC/3320/NS-2/Green 1/Green 2/Green 1V

Toyota CVTF TC/FE

VW/Audi TL 52180(G-052-180)/TL 52116(G-052-516)

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

Toda Oil Japan 15/9 Buddhamonthon Sai 2 Rd., Taweewattana Bangkok 10170, Phone: Sales +66 (80)515-2424

Website: www.todaoiljapan.com E-mail sales@todaoiljapan.com

Typicals

| | |
|--------------------------------------|------|
| Density @15 °C, kg/l | 0.86 |
| Viscosity @40 °C mm ² /s | 34 |
| Viscosity @100 °C mm ² /s | 7.22 |
| Viscosity Index | 183 |
| Pour Point, °C | -45 |
| Flash Point COC, °C | 190 |
| Colour | Red |

Packing Size 1 liter, 5 liters, 18 liters, 200 liters

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

Toda Oil Japan 15/9 Buddhamonthon Sai 2 Rd., Taweewattana Bangkok 10170, Phone: Sales +66 (80)515-2424

Website: www.todaoiljapan.com E-mail sales@todaoiljapan.com