

# TODA 4T Superbike Fully Synthetic

## Product Descriptions

TODA 4T Superbike Fully Synthetic is fully synthetic motor oil of outstanding quality developed for high performance four-stroke engines synthetic oil recommended for four-stroke engines.

## Quality Attributes

- Exceptional thermal stability to help resist oxidation and high-temperature degradation.
- Outstanding protection against wear of engine and transmission components.
- Excellent low temperature flow characteristics to help.
- Excellent antirust and anticorrosion properties.
- Controlled frictional properties eliminate clutch slippage and improves drivability.
- Excellent dispersant and detergent properties.

## Applications

- Suitable for motorcycles which are compatible with wet clutches.

## Specifications

API SN

JASO MA2

## Typicals

SAE Grade Viscosity	10W-40
Density @15 °C, kg/l	0.85
Viscosity @40 °C mm <sup>2</sup> /s	90.6
Viscosity @100 °C mm <sup>2</sup> /s	14.3
Viscosity Index	164
Pour Point, °C	-44
Flash Point COC, °C	236

## Packing Size 1 liter

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

Toda Oil Japan 15/9 Buddhamonthon Sai 2 Rd., Taweewattana Bangkok 10170, Phone: Sales +66 (80)515-2424

Website: [www.todaoiljapan.com](http://www.todaoiljapan.com) E-mail: [sales@todaoiljapan.com](mailto:sales@todaoiljapan.com)