

TODA Benzine N Semi Synthetic 10W-30

Product Descriptions

TODA Benzine N Semi Synthetic 10W-30 is a semi synthetic engine oil designed to keep your engine running like brand new by providing exceptional wear protection, cleaning power and overall best performance.

Quality Attributes

- Fuel Economy
- Outstanding thermal and oxidative stability
- Excellent performance at low temperatures
- High Viscosity Index
- Active clean up
- Superior resistance to oil degradation

Applications

TODA Benzine N Semi Synthetic 10W-30 is suitable for use in automobile, gasoline engines where the manufacturer recommends an API SN or earlier specification.

Specifications

API SN

ILSAC GF-5

Typicals

Density @15 °C, kg/l	0.86
Viscosity @40 °C mm ² /s	66
Viscosity @100 °C mm ² /s	10.3
Viscosity Index	142
Pour Point, °C	-32
Flash Point COC, °C	220
Total Base Number, mgKOH/g	6.0

Packing Size 1 liter, 4 liters

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

Toda Oil Japan 15/9 Buddhamonthon Sai 2 Rd., Taweewattana Bangkok 10170, Phone: Sales +66 (80)515-2424

Website: www.todaoiljapan.com E-mail: sales@todaoiljapan.com