

TODA MT Truck Fully Synthetic 75W-90

Product Descriptions

TODA MT Truck Fully Synthetic 75W-90 is an extreme pressure gear oil. It is especially recommended for synchromesh transmissions where it provides full protection to components to ensure reliable operation and smooth gear changes.

Quality Attributes

- Superior cleanliness
- Excellent oxidation stability
- Extends the life of the transmission by protecting the gears and bearings against wear and pitting
- Outstanding Yellow Metal Protection
- Excellent wear protection reduces wear and prolongs gear life
- Wide synchroniser compatibility
- Compatible with normal mineral oil. No special flushing procedure needed when changing from mineral to synthetic oil

Applications

- Suitable for manual transmissions, synchromesh gearboxes and other applications which require API GL-4

Specifications

API GL-4

MAN 341 E2, Z2

ZF TE-ML 02B, 17A

Typicals

Density @15 °C, kg/l	0.89
Viscosity @40 °C mm ² /s	101
Viscosity @100 °C mm ² /s	15.4
Viscosity Index	162
Pour Point, °C	-54
Flash Point COC, °C	255

Packing Size 1 liter, 5 liters, 18 liters, 200 liters

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

Toda Oil Japan 15/9 Buddhamonthon Sai 2 Rd., Taweewattana Bangkok 10170, Phone: Sales +66 (80)515-2424

Website: www.todaoiljapan.com E-mail: sales@todaoiljapan.com