

TODA ATF Dexron III-H

Product Descriptions

TODA ATF Dexron III-H is a high performance, automatic transmission fluid designed to meet the service fill requirements for old and new vehicles. It provides reliable performance including smooth & consistent in all weather conditions and all-around lubrication protection of the transmission components.

Quality Attributes

- Friction modifiers improve transmission efficiency and shifting performance
- Exceptionally high oxidation resistance
- Excellent thermal and oxidation stability for long and consistent transmission performance
- Low temperature performance
- Dependable anti-wear and gear protection

Applications

- Passenger car automatic transmissions
- Heavy duty automatic transmissions
- Power steering units

Specifications

Dexron® III-H

Typicals

Density @15 °C, kg/l	0.86
Viscosity @40 °C mm ² /s	32
Viscosity @100 °C mm ² /s	7.0
Viscosity Index	176
Pour Point, °C	-46
Flash Point COC, °C	180
Colour	Red

Packing Size 1 liter, 5 liters, 18 liters, 200 liters

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

Toda Oil Japan 15/9 Buddhamonthon Sai 2 Rd., Taweewattana Bangkok 10170, Phone: Sales +66 (80)515-2424

Website: www.todaoiljapan.com E-mail: sales@todaoiljapan.com