

TODA MT Truck 80W-90

Product Descriptions

TODA MT Truck 80W-90 is an extreme pressure gear oil. It is especially recommended for synchromesh transmissions where it provides full protection to components to ensure reliable operation and smooth gear changes.

Quality Attributes

- Synchroniser compatibility
- Long drain intervals 160,000 km (MAN 341 Z2)
- Protection against rust and corrosion
- Easy gear change
- Good anti-wear and load carrying characteristics extend the life of components

Applications

- Suitable for manual transmissions, synchromesh gearboxes and other applications which require API GL-4

Specifications

API GL-4

MAN 341 E2, Z2

ZF TE-ML 02B, 17A

Typicals

Density @15 °C, kg/l	0.89
Viscosity @40 °C mm ² /s	159
Viscosity @100 °C mm ² /s	15.8
Viscosity Index	102
Pour Point, °C	-36
Flash Point COC, °C	205
Viscosity, Brookfield @ -40C, mPa.s (cP)	128,000

Packing Size 1 liter, 5 liters, 18 liters, 200 liters

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

Toda Oil Japan 15/9 Buddhamonthon Sai 2 Rd., Taweewattana Bangkok 10170, Phone: Sales +66 (80)515-2424

Website: www.todaoiljapan.com E-mail: sales@todaoiljapan.com